

BLUECARD GUARD TOUR SYSTEM



*BP-2002S
Guard Tour Data Collector*



*BLC-30N
Proximity Checkpoint Tag*



Communication Station



EM Proximity Key Tag

Guard Tour Data Collector

| | |
|------------------------------|---|
| <i>Card Reading</i> | <i>: Inductive / Non Contact</i> |
| <i>Card Format</i> | <i>: 125 Khz EMID</i> |
| <i>Maximum Reading Range</i> | <i>: 3.5 cm</i> |
| <i>Power Capacity</i> | <i>: > 330,000 readings</i> |
| <i>Battery Type</i> | <i>: CR123A 3V Lithium Battery</i> |
| <i>Waterproofing</i> | <i>: Completely sealed</i> |
| <i>PC Connection</i> | <i>: Wireless Communication Station</i> |
| <i>Working Temperature</i> | <i>: - 40°C to 70°C</i> |
| <i>Working Humidity</i> | <i>: 0 - 95%</i> |
| <i>Dimensions</i> | <i>: 120 x 35 x 26 mm</i> |
| <i>Weight</i> | <i>: 142g ± 5g</i> |

Communication Station

| | |
|---------------------------------|-----------------------------------|
| <i>Size</i> | <i>: 159 x 79 x 33 mm</i> |
| <i>Connection with Readers</i> | <i>: RFID Wireless Connection</i> |
| <i>Connection with Computer</i> | <i>: USB</i> |
| <i>Card Reading Format</i> | <i>: EMID RFID</i> |
| <i>Working Temperature</i> | <i>: - 20°C to 70°C</i> |
| <i>Working Humidity</i> | <i>: 0 - 95%</i> |

Based on advanced RFID technologies, our complete Guard Tour System makes patrolling more efficient and reliable with its RFID reader, data transmitter and management software. It is also great for other application including data collecting, monitoring, time and place control system, etc. History database can be provided as well.

Reports can be exported into PDF file, Excel file, CSV file or sent in an email!